



Slat Top Conveyors



The Robotunits Slat Top Conveyor:
Efficient conveyor technology for complex layout designs

Slat Top Conveyors

Reliable, flexible and efficient

Discover the flexible and reliable solution for transporting materials over longer distances: Our Slat Top Conveyors are ideal for complex conveyor layouts with multiple curves. Whether in the packaging industry, logistics, food industry, waste management or automotive industry, the efficient,


reliable and low-maintenance conveyors seamlessly integrate into your production and logistics processes. With their robust design and wide range of applications, our conveyors ensure seamless workflows, increased productivity and sustainable optimization of your processes.

Facts

- Compact conveyor technology with extremely tight curve radii
- Long distances with just one drive unit
- The pulley is flush with the frame

Benefits

- Optimal customization for spatial and material flow conditions
- Energy efficiency
- Easy transfer of products



Technical data

Frame width:	87 mm, 124 mm, 195 mm
Chain width:	82.6 mm, 114.3 mm, 190.5 mm
Min. curve radius:	Chain width 82.6 mm = 200 mm Chain width 114.3 mm = 200 mm Chain width 190.5 mm = 610 mm
Speed:	5 m/min to 30 m/min

Max. conveyor length: approx. 15,000 mm *
Max. conveyor load: approx. 150 kg *
* depending on the conveyor layout


Alternative widths and speeds available upon request.

Slat Top Conveyors

Layout, drive and control


Special extrusion:

- Mounting options for sensors, side guides and stands



Drive:

- 230/400 V drive
- Chain sag for optimal tensioning of the slat top chain



Pulley:


- Special pulley for optimal movement of the slat top chain
- Flush with the frame

Three frame widths


- The optimal frame width for every application, depending on the weight, speed, inclination, conveyor layout, etc.



Frame width 87 mm



Frame width 124 mm



Frame width 195 mm

Slat top chain:

- Various chain widths
- Extremely tight curve radii possible
- Chain links are individually interchangeable



Chain width 82.6 mm | curve radius 200 mm



Chain width 114.3 mm | curve radius 200 mm



Chain width 190.5 mm | curve radius 610 mm

Turnkey Conveyor Solutions

Our Slat Top Conveyors are extremely versatile: they can be used in both indexing and accumulation operation or in other turnkey solutions that have already proven successful for our belt, modular belt and timing belt conveyors.

This enables us to offer you customized solutions for a wide range of conveying requirements and to provide you with efficient and versatile conveyor technology that is tailored to your individual requirements.



Standardized application solutions customized to your needs

The field-tested applications from the Robotunits Modular Automation System offer ingenious solutions for the simple optimization of your processes.



Discover applications
<https://robotunits.com/en/applications/>



Outstanding Quality



Uncompromising Service



Fastest Delivery Times